

WICANDERS W 336 TECHNICAL INFORMATION

APPLICATION AREA

Dispersion-based adhesive for laying Wicanders Hydrocork on absorbent indoor floors.

SPECIAL PROPERTIES

- solvent-free *
- suitable for castor chairs
- very low in emission**
- suitable for radiant-heated subfloors

* Solvent free according to the definition of the TRGS 610

** very low in emissions according to emission class EMICODE EC1 PLUS

TECHNICAL DATA

Raw material base: acrylate dispersion

Cleaning agent: water, before the adhesive starts to dry

Method of application: with notched trowel TKB A2

Consumption: 350-400 g/m²

Airing time: approx.: 20 minutes

Open time: 1 hour not below 5°C, sensitive to frost

Storage temperature: not below 5° C, sensitive to frost

Storage time: 12 months at room temperature

GISCODE: D1

EMICODE: EC1 PLUS

SUBFLOORS

The subfloor must be leveled and the climatic conditions must be level, permanently dry, solid and free from cracks, dirt and adhesion inhibiting substances.

Make sure, the subfloor is well absorbent. If the subfloor shows low absorbency or no absorbency, apply a high quality cement based levelling compounds in a minimum thickness of 2-3 mm. The technical information on the primers and levelling compounds must be heeded.

WICANDERS ADHESIVE W 336 IS NOT COMPATIBLE WITH LATEX LEVELLING COMPOUNDS

USAGE

Stir adhesive well before using. Using a notched trowel, apply evenly on the subfloor, avoiding adhesive pools.

Lay down the tiles on the fresh adhesive without waiting and press them well.

Make sure, the adhesive ridges are compressed completely to an even adhesive film. Roll with a 50 kg multipart roller after a short period. Again approx. 1 hour to reroll. If necessary, put a weight on top of troublesome edges.

IMPORTANT

Do not use this adhesive in rooms with temperature below 18°C. With cold weather conditions, warm up the adhesive in the heated room before it is needed for the application.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which are beyond our control, preclude any claims based on this data. We therefore recommend doing sufficient trials. Going through the installation instructions and the applicable codes are a must. We gladly provide technical advice.