SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

Adopen

Mah. 21. Cadde No:3, 07040 Aosb 2. 07040, Dösemealti, Turkev

For the following product(s):

Vinyl Tile:

3.3 mm SPC + 1.5 mm IXPE - 12 mil (300 micron), 3.4 mm SPC + 1 mm IXPE - 20 mil (500 micron), 4.0 mm SPC + 1 mm IXPE - 12 mil (300 micron), 4.0 mm SPC + 1 mm IXPE - 20 mil (500 micron), 6.0 mm SPC + 1 mm IXPE - 20 mil (500 micron), SPC Flooring 4mm +1mm IXPE with underlayment 0,15mm Wear Layer, SPC Flooring 4mm +1mm IXPE with underlayment 0,30mm Wear Layer, SPC Flooring 4mm +1mm IXPE with underlayment 0,55mm Wear Layer, SPC Flooring 4mm 0,15mm Wear Layer without IXPE underlayment, SPC Flooring 4mm 0.30mm Wear Layer without IXPE underlayment, SPC Flooring 4mm 0.55mm Wear Layer without IXPE underlayment




The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

FloorScore®

Indoor Air Quality Certified to SCS-105 Version 4.2 – 2023

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m3 (in



Registration # SCS-FS-05915

Valid from: May 01, 2025 to January 31, 2026

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.





Diana Kirsanova Phillips, Chief Assurance Officer. SCS Global Services